



Novolence[®] water-saving hand shower

- Strong turbulence water jet
- G1/2 connection fits any usual shower hose
- Punched disc protects against limescale
- Saves up to 65% water and energy
- No maintenance necessary

The Novolence[®] shower head ensures a maximum of comfort and a minimum of water consumption while having a shower. The innovative, patented 3-hole-nozzle made it possible to achieve a completely new level of performance regarding shower comfort and water jet characteristics.

The Novolence[®] shower head has three accurately calculated orifice outlets. That makes the »Novolence Shower Head« insensitive against lime-scale and blockage. This construction ensures that the water jet is mixed with much oxygen, also at low pressure, and makes the jet very comfortable and smooth so that the user will not recognize a difference to an ordinary shower head.

Moreover, flow rate and shower pattern can be adjusted according to your personal preference by changing the turbulence and punched disc (2, 3, 4 or 12 holes as required).

Spray pattern:







Novolence[®] water-saving hand shower

Dimensions:




Flow volume:

The Novolence $^{(\!8\!)}$ shower head is available in different versions concerning the flow volume. The water jet and flow volume are influenced by varying the punched disc and turbulence insert.

model	tapered insert	disc (number of holes)	flow volume
201x	big	3	12 l/min
202x	small	3	7,8 l/min
203x	big	12	11,6 l/min
204x	small	2	6,6 l/min
206x	big	4	9,5 l/min

Spare parts:

model	item
T652	tapered insert 4,8 mm
T653	tapered insert 3,6 mm
T654	punched disc 3-hole 2,9 mm
T655	punched disc 12-hole 1,5 mm
T657	punched disc 2-hole 2,5 mm
T695	decor ring anthrazit (RAL 7016)
T658	punched disc 4-hole 2,0 mm
T691	decor ring blue (RAL 5017)
T692	decor ring grey (RAL 7037)
T694	decor ring green (RAL 6024)
T690	decor ring red (RAL 3020)



Colors:

The Novolence[®] shower head is available in white (RAL 9010) and chrome. On minimum orders of 5.000 pcs. the Novolence[®] shower head can be delivered in other RAL colors, matt chrome and matt gold.

Number "x" in the left-hand list must be replaced by one of the numbers below, which each stand for a color.

x = 0 = white

Technical specifications:

scope of delivery	1x gasket 19 x 13 x 2 mm EPDM 1x gasket 18,5 x 12 x 1,5 mm fiber composite
tests & standards	complies with the requirements of TrinkwV
materials	handle, mouthpiece: ABS, (optionally chrome-plated) tapered insert, punched disc: POM
total length	approx. 210 mm
weight	white: approx. 125g chrome: approx. 131g
guarantee	2 years



x = 5 = chrome-plated